


balkstaal

breedflensbalken, HEA

leveringsvoorwaarden: NEN-EN 10025-1 en -2
 toleranties: NEN-EN 10034; DIN 1025/3
 max. handelslengte: 28 m



profiel nr.	G ₈ kg/m	A mm ²	h mm	b mm	t _w mm	t _f mm	A _L m ² /m	I _y x10 ⁴ mm ⁴	W _{y,el} x10 ³ mm ³	I _z x10 ⁴ mm ⁴	W _{z,el} x10 ³ mm ³	profiel nr.
100	17,0	2124	96	100	5	8	0,561	349	72,8	134	26,8	100
120	20,3	2534	114	120	5	8	0,677	606	106	231	38,5	120
140	25,1	3142	133	140	5,5	8,5	0,794	1033	155	389	55,6	140
160	31,0	3877	152	160	6	9	0,906	1673	220	616	76,9	160
180	36,2	4525	171	180	6	9,5	1,02	2510	294	925	103	180
200	43,1	5383	190	200	6,5	10	1,14	3692	389	1336	134	200
220	51,5	6434	210	220	7	11	1,26	5410	515	1955	178	220
240	61,5	7684	230	240	7,5	12	1,37	7763	675	2769	231	240
260	69,5	8682	250	260	7,5	12,5	1,48	10455	836	3668	282	260
280	77,8	9726	270	280	8	13	1,60	13673	1013	4763	340	280
300	90,0	11253	290	300	8,5	14	1,72	18263	1260	6310	421	300
320	99,5	12437	310	300	9	15,5	1,76	22929	1479	6985	466	320
340	107	13347	330	300	9,5	16,5	1,79	27693	1678	7436	496	340
360	114	14276	350	300	10	17,5	1,83	33090	1891	7887	526	360
400	127	15989	390	300	11	19	1,91	45069	2311	8564	571	400
450	142	17803	440	300	11,5	21	2,01	63722	2896	9465	631	450
500	158	19754	490	300	12	23	2,11	86975	3550	10367	691	500
550	169	21176	540	300	12,5	24	2,21	111932	4146	10819	721	550
600	181	22646	590	300	13	25	2,31	141208	4787	11271	751	600
650	193	24164	640	300	13,5	26	2,41	175178	5474	11724	782	650
700	208	26048	690	300	14,5	27	2,50	215301	6241	12179	812	700
800	229	28583	790	300	15	28	2,70	303443	7682	12639	843	800
900	256	32053	890	300	16	30	2,90	422075	9485	13547	903	900
1000	277	34685	990	300	16,5	31	3,10	553846	11189	14004	934	1000